

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 918 178 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:

26.05.1999 Bulletin 1999/21

(51) Int. Cl.<sup>6</sup>: **F16K 27/00**

(21) Application number: **98309558.9**

(22) Date of filing: **23.11.1998**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**

Designated Extension States:

**AL LT LV MK RO SI**

(30) Priority: **21.11.1997 GB 9724540**

(71) Applicant: **Carver plc**

**Brownhills, Walsall, West Midlands WS8 7ES  
(GB)**

(72) Inventors:

- **Ford, Christopher John Charles**  
**Lichfield WS13 6QW (GB)**
- **Bryer, Keith Nigel**  
**Pelsall, Walsall WS3 4EW (GB)**

(74) Representative:

**Skerrett, John Norton Haigh et al**  
**H.N. & W.S. SKERRETT**  
**Charles House**  
**148/9 Great Charles Street**  
**Birmingham B3 3HT (GB)**

(54) **Fluid flow control valve assembly**

(57) A fluid flow control valve assembly includes a first valve (79) having a maximum flow rate, at least equal to the maximum flow rate required, connected in parallel to a number of further valves (65, 66, 67, 68) of lesser flow rates to allow flow rate to be chosen by selective operation of the further valves. The assembly is of sandwich construction including a number of non-ferrous foil lamellae (66, 63, 71) and spacer lamellae (60, 62, 70). Each valve has a valve seat and a valve member, both of which are provided on the foil lamellae. Chambers are bounded by the spacer lamellae and separated by the foil lamellae. The movable valve members (79, 65, 66, 67, 68) carry armatures so as to be movable by externally applied magnetic flux.

**EP 0 918 178 A2**

## Description

[0001] This invention concerns fluid flow control valve assemblies, for controlling the flow of fluid under pressure from an inlet to an outlet.

[0002] For those instances in which the fluid is a fuel e.g. propane or butane, for an appliance, e.g. a caravan space heater or water heater, there are a multiplicity of pertinent regulations which stipulate requirements concerning shut-off time, resistance to overpressures and back pressures, overheating, combustibility etc. and there are an equal number of commercial requirements especially those relating to cost, size mass and controllability.

[0003] In order to meet the regulatory requirements, it has hitherto been necessary to engineer and combine together in a compound unit or to install in series two different forms of flow control valve assembly, e.g. an on/off valve and a flow modulating valve such as a needle valve, which valves can be engineered from materials and with sufficient precision to meet these requirements. However, the cost of such compound units and the installed cost of series of valves is considerable as are the sizes and masses. Furthermore, the energy levels for controlling such valves can be high in the context of the available battery power in a caravan and other mobile or free standing applications.

[0004] In order to solve the problems of meeting the regulatory requirements and the commercial requirements simultaneously, the present invention provides a fluid flow control valve assembly comprising a plurality of valves, each having a valve seat and a movable valve member, in a body provided with an inlet and an outlet, which is characterised in that:

- a) the body is of sandwich construction comprising a plurality of non-ferrous foil lamellae and a plurality of thicker spacer lamellae,
- b) the valve seats and valve members are formed in or provided on the foil lamellae,
- c) chambers are bounded by the spacer lamellae and are separated by the foil lamellae,
- d) the movable valve members carry armatures so as to be movable by externally applied magnetic flux.

[0005] The valves preferably comprise a first valve having a maximum flow rate equal to, and preferably well in excess of, the maximum flow required (at a predetermined nominal pressure) and at least two further valves of lesser flow rates.

[0006] In one embodiment, two further valves of lesser flow rates e.g. of 0.33 and 0.66 of the maximum flow rate, and in another embodiment four further valves of lesser flow rates e.g. of 0.1, 0.2, 0.3 and 0.4 of the maximum flow rate, are provided for selective actuation individually or in selected combination to give incremental modulation of the flow.

[0007] The valve actuating magnetic flux may be provided by manually movable permanent magnets mounted so as to be displaceable between valve open positions proximal to the body and valve closed positions spaced from the body.

[0008] However, the valve assembly is particularly suitable for electromagnetic control by means of individually energisable coils or solenoids mounted on or in abutment with the body.

[0009] The foil lamellae are preferably foils of the hard resiliently flexible material e.g. phosphor bronze or non-magnetic stainless steel. The valve seats are preferably the surfaces of one of the foils, which surround fixed diameter openings in that one of the foils. The movable valve members preferably comprise spring tongues formed from the other one of the foils and valve heads of a compressible rubber or plastics material mounted on the spring tongues or on the armatures carried by the spring tongues.

[0010] The spacer lamellae preferably provide partitions which can be cut away to connect a plurality of chambers together. Preferably, at least two of said chambers serve as common manifolds for the further valves. The spacer lamellae are preferably formed from a hard durable material, such as aluminium.

[0011] One of said foils preferably provides a filter mesh between one of said chambers, namely an inlet chamber, and another of said chambers, namely a feed chamber for the first valve.

[0012] The valve assembly and solenoids may be mounted on a printed circuit board carrying control circuitry for energisation of the solenoids.

[0013] The valves are preferably arranged so that they tend to be held closed by the tongues and/or by the applied pressure of the fluid.

[0014] The tongues may be simple elongate blades or leaves, but each armature is preferably carried by a pair of M or W shaped tongues so as to be maintained in a plane parallel to the plane of the foil.

[0015] Assemblies according to the present invention confer considerable advantage over prior art arrangements. A particular advantage is the considerable recharged power consumption compared to known arrangements: typically of the order of milliwatts. This makes assemblies according to the invention particularly useful for use in mobile and free standing appliances, where dry batteries may be employed, and other installations where it is undesirable or inconvenient to use a mains power supply.

[0016] The invention will be described further, by way of example, with reference to the accompanying diagrammatic drawings, wherein:-

FIGURE 1 shows a perspective view of a fluid flow control valve assembly according to the invention;

FIGURE 2 shows a longitudinal sectional diagram of the valve assembly of FIGURE 1 taken along the

line B-B of FIGURE 1;

FIGURE 3 shows a transverse cross-sectional view of the assembly of FIGURE 1 taken along the line A-A of FIGURE 1;

FIGURE 4a to 4i show respectively plan views of the lamellae of the valve assembly of FIGURES 1 and 2;

FIGURE 5 shows a detail of one valve of the assembly of FIGURES 1 to 4 in enlarged view;

FIGURE 6 shows two perspective views of the valve seat of FIGURE 5;

FIGURE 7 shows a detail of a rivet of the assembly of FIGURES 1 to 4 in enlarged view;

FIGURE 8 shows an exploded perspective view from above of a second embodiment of a valve assembly;

FIGURE 9 shows a partially exploded perspective view from underneath of the embodiment illustrated in FIGURE 8; and

FIGURE 10 shows a perspective view of a spring tongue.

[0017] Referring to FIGURES 1 to 7 (in which the same reference numerals are used throughout to identify corresponding components of the assembly), the valve assembly has a body 10 of sandwich construction comprising a plurality of lamellae clamped together by rivets 11, although other fasteners such as threaded fasteners or spring clips could be employed. The interface joints between the lamellae are sealed.

[0018] The lamellae include a first valve plate 13, first valve foil (flange plate) 14, a second valve plate (inlet/outlet spacer) 15, a second valve foil (valve port foil) 16, a third valve plate (valve spacer (17)), a third valve foil (spring plate 18), a fourth valve plate (feed manifold spacer) 19, a fourth valve foil plate (feed manifold spacer) 19, a fourth valve foil (backplate) 20 and a final spacer 21.

[0019] In association with the lamellae are three solenoids 1, 2 and 3 which extend between the backplate 20 (through the spacer 21) and three coil supports 4, secured to the backplate 21. A further, floating, coil support 5 is also provided, it is spaced from the coil support 4 by way of a layer of foam material 6.

[0020] The first valve plate 13 and flange plate 14 include a gas inlet 25 and a gas outlet 26. The inlet/outlet spacer 15 comprises a short e.g. 4 mm slice of a hollow aluminium extrusion providing four internal webs 30, 31, 32 and 33 of which in the spacer 15 only the webs 30 and 32 are left intact.

[0021] The valve port foil 16 is formed from a sheet of phosphor bronze e.g. by etching to provide a mesh grid or filter structure 27, an inlet valve opening 28, a transfer port opening 29, and two progressively graduated metering valve openings 34 and 35. The valve spacer 17 is a second slice of the extrusion with a single internal web 36 left intact. The spring plate 18 is formed from the same sheet material and by the same means as the foil 16 so as to provide a series of spring tongues 44, 45 and 46 each of which carries an elastomeric valve member 39, 36, 37 on the side facing the foil 16 and a ferromagnetic armature 40 on the side facing the backplate 20. The valve member 37 is retained by way of an armature stud 38 which passes through the spring plate 18.

[0022] Opposite ends of each spring tongue 44, 45, 46 are secured with rivets 47 to the feed manifold spacer 19. This is shown in detail in FIGURE 8.

[0023] The feed manifold spacer 19 is a further slice of the aluminium extrusion with all the webs intact. The backplate 20 is formed from the same sheet material as are the foils 16 and 18. The final spacer 21 is formed from a slice of another aluminium extrusion.

[0024] When the lamellae are clamped together to form the body 10, the valve plate 13, flange plate 14, extrusion 15 and foil 16 together define an inlet chamber 50 which extends from the inlet 25 to the filter screen 27, a transfer chamber 51 leading from the inlet valve opening 28 to the transfer port 29, and an outlet flow manifold 52 leading from the valve openings 34 and 35 to the outlet 26. The foils 16 and 18 with the spacer 17 therebetween define an on/off valve chamber 53, in which the valve member 39 is accommodated, an extension 54 of the transfer passage and a common valve chamber 55 which accommodates valve members 36 and 37. The foil 18, spacer 19 and backplate 20 define further chambers 56.

[0025] Each valve member 39, 36 and 37 is of greater diameter than its respective valve opening 28, 34 and 35 so that the surrounding portion of the surface of the foil 16 serves as a seat with which the valve member 39 is normally held in sealing abutment by a bias provided by its spring tongue and any pressure in the chamber 53 or 55 which is in excess of the pressure in the passage 51 or manifold 52.

[0026] Sealing gaskets or coatings on the confronting surfaces of the lamellae and structural formations to give the necessary rigidity to the lamellae are not shown.

[0027] The backplate 20 is preferably of the same material as the foils so as to be of minimum thickness to minimise the distances between the cores of the solenoids 1, 2 and 3 and their respective armatures 40. The backplate 19 also provides a stop to limit movement of the yokes 40 and thus the opening movements of the valve members 39. It will also be appreciated that the spring tongue 44 with its valve member 39 and yoke 40 together with the inlet valve opening 28 form an inlet

valve; and that the spring tongues 45 and 46 together with their respective valve members, armatures and valve openings 34 and 35 form a series of two further valves selectively energisable by the solenoids. The openings 34 and 35 are graduated so as to respectively pass 0.33 and 0.66 of the amount of fluid which can pass through the port or opening 28 at the same fluid pressure.

[0028] Thus, from the foregoing it will be appreciated that fluid entering the valve assembly 10 through inlet 25 is directed through filter mesh 27 into chamber 53. The flow of the fluid is then interrupted by the on/off valve formed by opening 28 and valve member 39 which is normally kept in sealing contact with opening 28 by action of the spring plate 18.

[0029] To allow gas to flow through the assembly solenoid 1, and one of either solenoids 2 or 3, must be energized.

[0030] When solenoid 1 is energized armature 40 is drawn towards the solenoid 1, pulling the valve member 30 away from the opening 28. The spring tongue 46 is generally M-shaped and allows the armature 40 to move towards the solenoid 1 with a parallel motion. Fluid can then flow through opening 28 and 29 and into chamber 55. Flow from chamber 55 is via the further valves, formed by openings 34 and 35 and their respective valve members 36 and 37 to chamber 52 and hence to the outlet 26. The rate of flow through the assembly depends upon whether solenoids 2 or 3 or both are energized. Energizing one solenoid allows 0.33 of the maximum flow of fluid to pass, energizing the other, 0.66 to pass, and energizing both, the maximum flow to pass.

[0031] An alternative valve assembly having a greater number of valves e.g. one on/off valve and four further valves is preferably arranged so that a progressive variation of the fluid flow can be achieved by selective energisation of the further valves e.g. if four further valves are provided with four valve ports should be graduated to respectively pass 0.1, 0.2, 0.3, 0.4 of the amount of fluid which can pass through the on/off valve port at the same fluid pressure.

[0032] Such an alternative assembly is shown in FIGURES 8 and 9. Referring to FIGURES 8 and 9 the assembly comprises a number of lamellae. Particularly it comprises a flange plate 60, valve port foil 61, valve spacer 62, spring plate 63, five valve members 64 to 68 including rubber tipped sealing pads 69, a feed manifold spacer 70 and a backplate 71.

[0033] In use the lamellae are held in sealing contact with each other by rivets 72, as shown in FIGURE 9.

[0034] Some of the spacer lamellae include flanged projecting feet 73 to engage in slots 74 to locate the body of the assembly on a printed circuit board 75 which carries mountings 76 for a number of valve energizing solenoids 77, identified by suffix letters a to e.

[0035] Each solenoid is associated with a valve of the assembly. Solenoid 77a is associated with the on/off

valve and solenoids 77b to 77e with the four flow control valves.

[0036] The operation of this embodiment is similar to that of the first embodiment illustrated in FIGURES 1 to 7. Fluid is admitted through an inlet 78 in the flange plate, from which it flows through a mesh in the valve port foil 61 to the on/off valve which is closed by rubber tip 79, and held in the closed position by action of the spring plate 63. To allow a flow of gas pass through the assembly the on/off valve is opened by activating solenoid 77a which allows gas to flow to each of the further valves which are graduated to allow passage of 0.1, 0.2, 0.3 and 0.4 of the amount of gas which can pass through the on/off valve. Selective operation of the solenoids therefore allows the amount of gas flowing through the valve to be controlled between 0.1 and the full amount which can pass through the on/off valve, in 0.1 increments.

[0037] From the flow control valves gas flows to the outlet 80.

[0038] The invention is not confined to details of the foregoing examples and many variations are possible within the scope of the invention. For example the spring tongues could be of simple straight blade form or each armature could be carried at opposite ends by spring tongues of M or W shape which ensure that the armature has a parallel motion when moved by its solenoid.

[0039] A perspective view of a spring tongue similar, but not identical, to those of the assemblies illustrated in FIGURES 1 to 9, is shown in FIGURE 10.

[0040] Furthermore the valve member 39 need not be as shown but could be a thick planar body, adhered to the spring tongue, as shown in FIGURE 10, instead of being anchored to the armature 40 via a port extending through an aperture.

#### Claims

1. A fluid flow control valve assembly comprising a plurality of valves, each having a valve seat and a movable valve member, in a body provided with an inlet and an outlet, which is characterized in that:


- (a) the body is of sandwich construction comprising a plurality of non-ferrous foil lamellae and a plurality of thicker spacer lamellae,
- (b) the valve seats and valve members are formed in or provided on the foil lamellae,
- (c) chambers are bounded by the spacer lamellae and are separated by the foil lamellae, and
- (d) the movable valve members carry armatures so as to be movable by externally applied magnetic flux.

2. A fluid flow control valve assembly according to Claim 1, wherein the valves comprise a first valve having a maximum flow rate at least equal to the

maximum flow required (at a predetermined nominal pressure) and at least two further valves of lesser flow rates.

tongues are arranged so that the armature has a parallel motion when moved by a magnetic flux.

3. A fluid flow control valve assembly according to Claim 2, wherein two further valves of 0.33 and 0.66 of the maximum flow rate are provided. 5
4. A fluid flow control valve assembly according to any preceding claim further comprising individually energisable solenoids mounted on or in abutment with the body. 10
5. A fluid flow control valve assembly according to any preceding claim, wherein the foil lamellae comprise foils of phosphor bronze or non-magnetic stainless steel. 15
6. A fluid flow control valve assembly according to any preceding claim, wherein the valve seats are formed by the surfaces of one of the foils, which surround openings in that one of the foils. 20
7. A fluid flow control valve assembly according to any preceding claim, wherein the movable valve members comprise spring tongues formed from the other one of the foils and valve heads of a compressible rubber or plastics material mounted on the spring tongues or on the armatures carried by the spring tongues. 25 30
8. A fluid flow control valve assembly according to any preceding claim, wherein the spacer lamellae provide partitions which can be cut away to connect a plurality of chambers together. 35
9. A fluid flow control valve assembly according to any preceding claim, wherein the spacer lamellae are formed from aluminium. 40
10. A fluid flow control valve assembly according to any preceding claim, wherein one of said foils provides a filter mesh between one of said chambers and another of said chambers. 45
11. A fluid flow control valve assembly according to Claim 7, wherein the valves are arranged so that they tend to be held closed by the tongues and/or by the applied pressure of the fluid. 50
12. A fluid flow control valve assembly according to Claim 7 or any of Claims 8 to 11 when appendant, directly or indirectly, to Claim 7 wherein each armature is carried by a pair of M or W shaped tongues. 55
13. A fluid flow control valve assembly according to Claim 7 or any of Claims 8 to 12 when appendant, directly or indirectly, to Claim 7 wherein the spring

Fig 1




Fig 2







Fig 3








Fig 4d




Fig 4e




Fig 4f




Fig 4g




Fig 4h









Fig 4i








Fig 10

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 918 178 A3

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
04.10.2000 Bulletin 2000/40

(51) Int. Cl.<sup>7</sup>: F16K 27/00

(43) Date of publication A2:  
26.05.1999 Bulletin 1999/21

(21) Application number: 98309558.9

(22) Date of filing: 23.11.1998

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventors:  
• Ford, Christopher John Charles  
Lichfield WS13 6QW (GB)  
• Bryer, Keith Nigel  
Pelsall, Walsall WS3 4EW (GB)

(30) Priority: 21.11.1997 GB 9724540

(74) Representative:  
Skerrett, John Norton Haigh et al  
Wilson Gunn Skerrett,  
Charles House  
148/9 Great Charles Street  
Birmingham B3 3HT (GB)

(71) Applicant: Carver plc  
Brownhills, Walsall, West Midlands WS8 7ES  
(GB)

## (54) Fluid flow control valve assembly

(57) A fluid flow control valve assembly includes a first valve (79) having a maximum flow rate, at least equal to the maximum flow rate required, connected in parallel to a number of further valves (65, 66, 67, 68) of lesser flow rates to allow flow rate to be chosen by selective operation of the further valves. The assembly is of sandwich construction including a number of non-ferrous foil lamellae (66, 63, 71) and spacer lamellae

(60, 62, 70). Each valve has a valve seat and a valve member, both of which are provided on the foil lamellae. Chambers are bounded by the spacer lamellae and separated by the foil lamellae. The movable valve members (79, 65, 66, 67, 68) carry armatures so as to be movable by externally applied magnetic flux.




Fig. 8

EP 0 918 178 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 98 30 9558

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.8)
X	US 3 547 139 A (BERKUM ROBERT A VAN) 15 December 1970 (1970-12-15) * abstract; figures 1-14 * * column 4, line 10 * * column 4, line 20 - line 23 * ---	1,2,4,6,8	F16K27/00
A	GB 2 163 834 A (DOWTY BOULTON PAUL LTD) 5 March 1986 (1986-03-05) * abstract; figures 1-6 * ---	1	
A	PATENT ABSTRACTS OF JAPAN vol. 007, no. 199 (M-240), 3 September 1983 (1983-09-03) & JP 58 099502 A (KAWASAKI JUKOGYO KK), 13 June 1983 (1983-06-13) * abstract * -----	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.8)  F16K F15B
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>10 August 2000</b>	Examiner <b>Billo, E</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (Pec01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 30 9558

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-08-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3547139 A	15-12-1970	NONE	
GB 2163834 A	05-03-1986	DE 3530420 A	13-03-1986
		ES 546459 D	16-07-1986
		ES 8609643 A	16-12-1986
		FR 2569813 A	07-03-1986
		IT 1182845 B	05-10-1987
		JP 61062606 A	31-03-1986
		NL 8502299 A	17-03-1986
JP 58099502 A	13-06-1983	NONE	